

IMPACT SAFETY BARRIER (DOUBLE) Ø100/70



DESCRIPTION

A Horizontal Impact Safety System (HISS) designed and certified to stop an impacting vehicle and redistribute the Impact Energy without damaging the floor. Certified safe for food and pharmaceutical environments. It's important to mention that the higher from floor an Impact Safety Barrier is the more Operating Space is required for a correct application. Guaranteed up to 10 years neither to break itself nor to break the floor in case of a maximum-limit impact. All accessories necessary for installation including a special high-quality anti-shrinkage concrete is included in the package.

Double HISS are designed to protect from vehicle parts protruding in an unconventional way like Euro Bins inside Meat Processing facilities. However, it's always the lowest Barrier that functions as Impact Safety System. The H770 and H1000 versions of this HISS are designed to segregate Pedestrian Ways from other areas inside a given production or logistics facility.

» SAFETY COMPLIANCE:

EU Directive 89/391/CEE

European Union directive with the objective to introduce measures to encourage improvements in the safety and health of workers at work.

IT Dlgs. 81/08 (unified safety charter)

Italian legislative decree concerning health and safety in the workplace, implementing European Directive 89/391/EEC

EU Regulation 852/2004/CE

European regulation describing the general requirements on the hygiene of foodstuffs applicable for all work environments where foodstuffs products are prepared and processed.

APPLICATIONS

- WALL PROTECTION • RACK PROTECTION
- COLUMN PROTECTION • MACHINE PROTECTION
- CONVEYOR PROTECTION • PARKING LOT PROTECTION
- ELEVATOR PROTECTION

TECHNOLOGY

FIXA BLOCK
SYSTEM BY STOMMPY

TECKLENE
TECHNOLOGY BY STOMMPY

TECHNICAL FEATURES

» IMPACT SAFETY BARRIER TECHNICAL FEATURES:

Material	Tecklene®	
Anchorage System	FIXA Block System®	
IP protection degree	IPX9K	
Food Safety Compliance	USA, UK ed Europa	
Available Heights (mm/in)	440 - 770 - 1000 / 17,32 - 30,31 - 39,37	
Available Lengths (mm/in)	1000 - 1500 - 2000 / 39,37 - 59,06 - 78,74	
Applicable on Metal Platforms	Yes	
Operating Temperature Range	-40 °C (-40 °F)	+50 °C (+122 °F)

» SAFETY COMPLIANCE:

EU Directive 89/391/CEE	European Union directive with the objective to introduce measures to encourage improvements in the safety and health of workers at work.
IT Dlgs.81/08 (unified safety charter)	Italian legislative decree concerning health and safety in the workplace, implementing European Directive 89/391/EEC
EU Regulation 852/2004/CE	European regulation describing the general requirements on the hygiene of foodstuffs applicable for all work environments where foodstuffs products are prepared and processed.